

Optical/Comms Test & Measurement



- Optical/Protocol Transport Test (800G)
- CFP/CFP2/CFP4/QSFP+/QSFP28 Stress Test
- Optical Switching, Mfg. Lab Test
- Optical Field Test
- Fiber inspection and test



www.tmi.yokogawa.com

- Optical spectrum analyzers / 350nm-5.5um
- Wavelength meter
- Multi Application Test System (MATS) – Grid Tunable Laser, LD, Optical Switches, VOA, Optical Sensor
- OTDR, OTLS



- WaveShaper Family (1ch – 16ch, S/C/L band)
- WaveAnalyzer – high resolution spectrum analyzer
- WaveShaper 1000/SP 1µm Programmable Single-Polarization Filter



www.lunainc.com

- Optical Vector Analyzer (OVA)
- High Resolution Backscatter Reflectometers (OBR)
- Tunable Lasers (Instrument and components)
- Fiber Fabry-Perot Tunable Filters



www.bristol-inst.com

- Wavelength Meters – fastest on the market
- Laser Spectrum Analyzers



www.polatis.com

- Optical Cross Connect Switches, non-blocking
- Compact form factor, SM and MM
- 4x4 up to 384x384 matrices available



- Fiber Lasers – CW and Pulsed: Green, 1064nm, 1550nm and 2000nm
- Amplifiers – CW and Pulsed: 1064nm, C&L Band (SM, PM), 2000nm
- Broadband Sources – 1064nm, ASE, Raman, 2000nm



<https://lunainc.com/general-photonics-now-luna-innovations>

- Polarization Controllers, Scramblers and Analyzers
- PMD & PDL generators and emulators
- OCT modules and components (MDL, PD, Couplers etc.)
- OFDR-1000 Hi-Resolution Reflectometer



- Optical Multi-Format Transmitter & Automatic Mach Zehnder BIAS Control
- Tunable lasers for C, L, C+L bands with narrow line widths
- Polarization maintaining multiplexer
- Optical DWDM decorrelator for XPolM and Coherent systems testing
- Low Cost Optical Spectrum Analyzer



- High resolution optical spectrum analyzer 10 MHz & dynamic range > 80 dB, C, C+L, L Band
- Option 230 – Measure spectrally-resolved state of polarization
- BOSA Lite with 20 MHz & > 80 dB dynamic range



NETWORKS

www.xenanetworks.com

- Layer 2-3 Gigabit Ethernet traffic generation
- Covers rates from 1GE up to 400GE, supports CFP4, QSFP28, QSFP+, CXP



www.mapleleafphotonics.com

- Optical Probing with modular design and small footprint
- Vertical and edge coupling
- Electrical probe support, manual & motorized alignment, thermal management with integrated SW control



the bandwidth company

www.shf-communication.com

- NRZ & PAM Pattern Generators up to 128 GBaud (256 Gbps) per Channel
- Error Analyzers up to 128 Gbps NRZ and 58 GBaud PAM4
- Arbitrary Waveform Generators up to 60 GSa/s
- Multiplexers (MUX) & Demultiplexers (DEMUX) up to 128 Gbps
- Digital-to-Analog Converters (DAC) up to 128 GBaud (256 Gbps)

Components



- High-power laser diodes
- Wavelengths range 630 nm to 1120 nm
- Broad Area Laser, Tapered Laser, Ridge Waveguide Laser/Fabry Perot Laser, DFB/DBR Laser



- Ultra-narrow linewidth laser diodes & modules
- 1550nm & 1064nm, up to 2W power, PM/SM fiber
- CW & FM modulation (up to 200 MHz)
- Low noise, high stability, highest reliability
- Applications: DAS, FOS, Doppler LIDAR, DTSS, Atomic Physics



- Optical MEMS switches and VOAs
- Switches: SM, MM, 1xN and MxN
- 2-D Galvanometers
- Rackmount, benchtop and component



Bringing Performance to Light!

- RF-over-Fiber Experts
- 50 GHz Analog Fiber Optic Links
- Antenna Remoting

www.linphotonics.com



- The Leader in Coherent Optical Communications.
- AC1200 providing 1.2Tbps of capacity in a 5"x7" footprint!
- CFP/CFP2 –DCO and CFP2-ACO coherent pluggables up to 200Gbps
- DSP and Silicon PIC solutions for you to integrate into your products!



- Delay Lines Interferometers
- 90° optical hybrids, Variable Optical Delay Line
- DWDM and Modal Mux/Demux
- Optical Switches. Custom optical assembly



- Fiber-Q™ Modulators and Drivers
- DFB Lasers and Modules
- Fiber Coupled Pump Laser
- Fused Fiber Optic Components



- Broadband RF & Microwave Amplifiers up to 67 GHz
- RF Switches, Filter and Attenuators
- Frequency Dividers & Multipliers
- Bias Tees and DC Blocks up to 110 GHz
- RF & Microwave Connectors and Cables up to 110 GHz



- iNbO3 Modulators: Phase, Intensity and Polarization Switches and Scramblers up to 40GHz
- Wide wavelength selection – 780nm - 2µm
- Modulator Drivers and Bias Controllers
- Reference/Analog Optical Transmitters
- Sub-nanosecond Optical Pulse Shapers



- GaAs Modulators – ideal for aerospace and satellite applications
- Broadband and IQ Modulators up to 45GHz



- Tunable chromatic dispersion emulator, compensator
- Chromatic Dispersion Emulator (up to 45,000 ps/nm)
- Narrow line width tunable laser (<1 kHz)



- 40-100GHz Photodetectors and Receivers, Single Ended and Balanced
- Integrated Balanced Receivers, DPSK, DQPSK, Coherent Solutions
- Optical Transceivers
- Optical Amplifiers
- Wavelength Management Components
- ROADMs
- WSS Elements

Services



Z-Poynt

www.zpoynt.com

- Bridging ideas with profitable products and applications
- Engineering and Project Management Consulting Services
- Serving communications, RF/microwave/fiber-optics, autonomous vehicles and satellite payload marketplaces
- Team of engineering, management and business resource professionals



Communication Components, Equipment and Services

www.xsoptix.com

- A Small Woman Owned Business Offering Distribution, Import and Reselling services
- Distributor for Finisar, ID Photonics, Aragon, Teraxion, eagleyard, monocrom, Sercalo, Kylia, Introspect, Pico, Optoscribe, Viavi handhelds and inspection equipment, Teledyne LeCroy and G&H

Digital, Electrical & RF/ μ wave Test



- SerDes Tester and BERT Functions, Pattern Generator Functions - 8 or 32 lanes, up to 32 Gbps NRZ & 56Gbps PAM4, handheld form-factor, USB Controlled, Software-Defined
- Test Solutions for: DDR4/DDR5 Memory Interfaces, PCIe, MIPI (Display, Touch, Imaging and Camera) and I3C
- MIPI DSI and DSI-2 Protocol Analyzer
- MIPI D-PHY and C-PHY Frame Grabbers



www.jtag.com

- Expert in Boundary Scan Test and Programming solutions
- 1149.1 and 1149.6 analog support
- PXI, Ethernet and USB Controllers



www.vaunix.com

- Low cost USB RF Synthesizers, Attenuators and Switches
- 50MHz to 20GHz
- GUI provided and Remote controllable



www.ladybug-tech.com

- USB RF Power Sensors (CW, Pulsed)
- 9 kHz to 40 GHz
- Fast (2,000 rdgs/sec), no-zero, no-cal



- Smart Power for optical components
- Multi-channel Voltage/Current sources
- Channel Counts from 8 to 120 channels



the bandwidth company

www.shf-communication.com

- Arbitrary Waveform Generators up to 60 GSa/s
- Synthesized Signal Generators (Synthesizers) up to 67 GHz
- Clock Distribution Instruments
- NRZ & PAM Pattern Generators up to 128 GBaud (256 Gbps) per Channel
- Error Analyzers up to 64 Gbps NRZ and 58 GBaud PAM4
- Arbitrary Waveform Generators up to 60 GSa/s
- Multiplexers (MUX) & Demultiplexers (DEMUX) up to 128 Gbps
- Digital-to-Analog Converters (DAC) up to 128 GBaud (256 Gbps)